



WEDOLiT CW 8006

Water-miscible, semi synthetic coolant



WEDOLiT CW 8006 is suitable for light to heavy cutting operations of steel, stainless steel, cast iron and aluminium.



Physical Properties Typical Data

Concentrate

Colour	Mineral oil content	Viscosity at 20°C: ASTM D 7042	Density at 20°C: ASTM D 7042	Copper corrosion: DIN 51759-1
Brown	15 %	101.0 mm ² /s	1.02	Not determined*

5% Solution

Colour	pH-value (tap water)	Corrosion protection DIN 51360-2	Refractometer factor (brix)	Conductivity (Deionised water)
White-beige	9.3	5 % grade 0	1.5	1480 µS/cm

Mineral oil	EP-additives	Chlorine	Boron	Amines	FAD
+	+	-	-	+	-

*Discolourations of non-ferrous metals should be examined in preliminary tests

Application Guidelines

The preparation of the emulsion is carried out by slowly adding the concentrate into water (drinking water quality) under thorough stirring. A more homogenous product is achieved by the use of automatic mixing systems.

Storage must be frost-free between 5 - 40°C.

The minimum durability is 12 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL: https://2trim.us/diw/?plr=CW-8006*en*eu

WEDOLiT CW 8006

©2017-2021 Master Fluid Solutions™ | 2021-07-25

Choose WEDOLiT CW 8006:

- Offers high cooling- and flushing properties with a very good wetting behaviour
- Contributes to a high tool life
- Very good application stability
- Almost free of foam
- Offers a good skin compatibility

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14
Düsseldorf, 40597
Germany

+49 211 77 92 85 - 0

info-eu@masterfluidsolutions.com

masterfluidsolutions.com/eu/en/

