

WEDOLiT K 856

Dewatering, short term RP 100°C



WEDOLiT K 856 is a dewatering fluid with slight corrosion protection properties that uses surface-active substances to displace both water and emulsions from the metal surface extremely quick. Even highly complex geometries can be dewatered efficiently. It is mainly used as an immersion bath at room temperature.

Fulfil all requirements regarding Altautorichtlinie 2000/53/EG. Not subject to the German VOC-regulation (VOC-guideline, 31 BImSchV) or to the Swiss regulation for VOC (Lenkungsabgabe VOCV Swiss).



Physical Properties Typical Data

| Parameter | Typical results | Tested according to |
|-------------------------|------------------------|-----------------------|
| Appearance: | Bright yellow, clear | Visual |
| Density at 15°C: | 0.81 g/cm ³ | ASTM D 7042 |
| Viscosity at 20°C: | 4.1 mm ² /s | ASTM D 7042 |
| Flash point: | > 100 °C | DIN EN ISO 2719 |
| Film weight: | 0.3 g/m ² | Dipping procedure |
| Film type: | Very slightly oily | Haptical |
| Dewatering effect: | ≤ 5 s | Internal test method |
| Water separation: | 4 min | Internal test method |
| Humidity test: | 7 cycles | DIN EN ISO 6270-2 AHT |
| Salt spray performance: | < 1 h | DIN EN ISO 9227 NSS |

Application Guidelines

Storage must be frost-free between 5 - 35°C.

The minimum durability is 12 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL: https://2trim.us/diw/?plr=K-856*en*eu

WEDOLiT K 856

©2020-2024 Master Fluid Solutions™ | 2024-04-25

Choose WEDOLiT K 856:

- Due to its strong dewatering effect, residues of flushing water or water containing fluids such as emulsions or synthetic coolants are removed from the metal surface
- Water/emulsions that enter the bath will settle on the bottom of the tank after a short period and can be drained off
- Development of a clear phase boundary between the water and the product, without forming an emulsion phase
- Due to its extreme dewatering properties, the product is ideal for workpieces that are additionally packaged with VCI foils
- Excellent bath-life
- Additive loss due to water contact: None

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14
Düsseldorf, 40597
Germany
+49 211 41 72 81 00

info-eu@masterfluids.com

masterfluids.com/eu/en/

