

TRIM[®] E720

Amine Free Machining & Grinding Emulsion

TRIM E720 is a high quality, universal soluble oil with a broad application range in machining and grinding of a wide range of materials. The high levels of both chemical and mechanical lubricity in this product handle the medium to heavy duty machining jobs on aluminium and stainless steel. The inhibitor package in TRIM E720 also makes it particularly suited to the machining of copper alloys without component staining or unsightly machine residues.

Soluble Oils



Geared up for production:

With superior lubricity and a higher oil content, TRIM emulsions provide a greater boundary layer between the tool and the material, and are ideal for heavy duty applications such as broaching, reaming, deep hole drilling, drilling, tapping and centerless grinding.

TRIM Emulsions work well for machining copper, yellow metals, steel alloys, cast aluminiums, wrought aluminiums and tough-to-machine titanium and nickel-based alloys.



Choose E720:

- Very stable formula provides long operational life with consistent performance
- Hard water tolerant
- Non-chlorinated and non-sulphurised extreme pressure (EP) additives control built-up edge (BUE)
- Fine soluble oil emulsion reduces carry-off for low total operating cost
- Fast wetting to get the fluid to the point of cut and fully coat the work piece and chips for superior corrosion prevention
- Will run effectively for long periods without the need for costly additives

E720 especially for:

Applications — centerless grinding, deep hole drilling, drilling, high-speed milling, high-speed turning, machining, milling, moderate-duty machining, reaming, sawing, tapping, thread forming, turning

Metals — aluminium, copper, steel alloys and yellow metals

Industries — automotive, bearing and general industry

E720 is free of — amines, boron, chlorine and formaldehyde releasers

TRIM[®] E720

Amine Free Machining & Grinding Emulsion

Application Guidelines

- Use higher concentrations for lower speed metal cutting operations where maximum lubricity is required and lower concentrations for operations requiring more cooling.
- Running at concentrations between 7 – 10% offers the best sump life and corrosion inhibition.
- For additional product application information, including performance optimisation, please contact your Master Fluid Solutions' Authorised Distributor at <https://www.masterfluids.com/eu/en/distributors/index.php>, your District Sales Manager, or call our Tech Line at +49 211 77 92 85 - 13.

Physical Properties Typical Data


Colour (Concentrate)	Brown
Odour (Concentrate)	Bland
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D93-08)	> 100°C
pH (Typical Operating as Range)	8.0 - 9.5
Coolant Refractometer Factor	1.0

Recommended Metalworking Concentrations

Light Duty	5.0% - 6.5%
Moderate Duty	6.5% - 8.5%
Heavy Duty	8.5% - 10.0%
Design Concentration Range	5.0% - 10.0%



Concentration by % Brix



% Concentration = Refractive Reading x Refractive Factor
Coolant Refractometer Factor % Brix = 1.0

Health and Safety

Request SDS



TRIM[®] E720

Amine Free Machining & Grinding Emulsion



Mixing Instructions

- Recommended usage concentration in water: 5.0% - 10.0%.
- To help ensure the best possible working solution, add the required amount of concentrate to the required amount of water (never the reverse) and stir until uniformly mixed.
- Use premixed coolant as makeup to improve coolant performance and reduce coolant purchases. The makeup you select should balance the water evaporation rate with the coolant carryout rate. Use our Coolant Makeup Calculator to find the best ratio for your machine: apps.masterfluids.com/makeup/.
- Use mineral-free water to improve sump life and corrosion inhibition while reducing carryoff and concentrate usage.

Ordering Information

20-litre pail

204-litre drum

1000-litre IBC

TRIM[®] E720 | ©2011-2024 Master Fluid Solutions[™] | 2024-04-26

Additional Information

- Use Master STAGES[™] Whamex[™] for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM[®] is a registered trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES[™] and Whamex[™] are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?i=eu_en_E720



Hasselsstraße 6-14
Düsseldorf, 40597
Germany
+49 211 41 72 82 00

info-eu@masterfluids.com

masterfluids.com/eu/en/

