
# WEDOLIT FW 7651

Water-miscible, fully synthetic coolant for the whole tube welding line









## Physical Properties Typical Data

		:	:	:
	0	0.0	0.00	
	0.0	0	0.0	0

## **Application Guidelines**

The preparation of the solution is carried out by slowly adding the concentrate into water (drinking water quality) under thorough stirring. A more homogenous product is achieved by the use of automatic mixing systems.

Storage must be frost-free between 5 - 40°C. The minimum durability is 12 months in an original sealed package.

#### Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL: https://2trim.us/diw/?plr=FW-7651\*en-th\*th

WEDOLIT FW 7651 ©2018-2024 Master Fluid Solutions™ | 2024-04-19





#### **Choose WEDOLIT FW 7651:**

- Due to its thermal stability, the product can be used in the whole production line (forming, welding, calibration, sawing)
- No emulsification of mineral oils and engine lubricants. Therefore, the application of an anticorrosion oil is possible (e.g. on the Turk's head of the tube welding engine in the manufacture of profiled tubes)
- Can be centrifuged without loss of active substances
- Removable with organic solvents or alkaline industrial cleaners
- A bright workpiece surface is obtained after annealing

#### Recommended mixing ratio

• Tube welding: from 4 - 6%

### **Health and Safety**

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

333/8 Moo 9, Bangpla, Bangplee Samutprakarn, 10540 Thailand +662 136 6319

thail and - info@master fluids.com

masterfluids.com/th/en-th/